



# tesa® 4348

## Product Information



Fleksibel maskeringstape for innendørs bruk

### Produktbeskrivelse

tesa® 4348 er en lett kreppet, rivebestandig standard maskeringstape med klebemasse av naturgummi, perfekt for innendørs malearbeid. Den smidige maskeringstapen kan rives for hånd, brukes i opp til 7 dager og er enkel å fjerne etter bruk. Takket være sin ypperlige klebestyrke muliggjør den klart definerte kanter under malearbeid og er et pålitelig verktøy for profesjonelle malere.

### Funksjoner

- Innendørs bruk
- Rene kanter for maling og lakk
- For glatte overflater
- For enkle maleoppgaver

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

- |                 |                      |                  |        |
|-----------------|----------------------|------------------|--------|
| • Bæremateriale | Papir (Lett kreppet) | • Total tykkelse | 140 µm |
| • Klebetype     | Naturgummi           |                  |        |

### Egenskaper / ytelsesverdier

- |                    |         |                    |           |
|--------------------|---------|--------------------|-----------|
| • Bruddforlengelse | 10 %    | • Hand tearability | very good |
| • Bruddstyrke      | 36 N/cm |                    |           |

### Klebekraft

- |                     |          |
|---------------------|----------|
| • Klebeevne på Stål | 3.3 N/cm |
|---------------------|----------|



# tesa<sup>®</sup> 4348

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=04348>