

storeys

TECHNICAL DATA SHEET

Roll-on-wall CoverStandard

Product description

| Material | ROLL-ON-WALL COVER STANDARD is a covering, heavy-duty glass veil. | | | | | | | | | | |
|--------------------------------|--|-----------------------|---------------------|-------------------------|---------------------|-------------------------|--------|----------------|----------------------|----------|----------|
| Use | Once applied to the wall, ROLL-ON-WALL COVER STANDARD hides small to medium-sized fibre glass structures and irregular surfaces at once, smoothing out wall surfaces. It is best used in high traffic areas and suitable for contract, as it allows avoiding filling old wall surfaces. Thus, renovation works can be carried out very time efficiently. | | | | | | | | | | |
| Properties | <ul style="list-style-type: none">• Covers irregular surfaces (small to medium-size)• Bridges cracks• Quick to a smooth wall:<ul style="list-style-type: none">→ no filling→ no sanding→ dust free→ no noise→ up to 75 % faster*• ideal as a wall liner and/or paint foundation | | | | | | | | | | |
| Certificates | <ul style="list-style-type: none">• complies with CE DIN EN 15102• flame retardant in accordance with DIN EN 13501-1 (A2 - s1, d0)• Standard 100 by Oeko Tex®• contains no allergeneous substances• A (VOC) | | | | | | | | | | |
| Roll size and packaging | <table><thead><tr><th><u>Article</u></th><th><u>Roll size</u></th><th><u>Weight approx.</u></th><th><u>Packing unit</u></th><th><u>Rolls per pallet</u></th></tr></thead><tbody><tr><td>660-15</td><td>1,00 x 15,00 m</td><td>375 g/m²</td><td>12 Rolls</td><td>48 Rolls</td></tr></tbody></table> | <u>Article</u> | <u>Roll size</u> | <u>Weight approx.</u> | <u>Packing unit</u> | <u>Rolls per pallet</u> | 660-15 | 1,00 x 15,00 m | 375 g/m ² | 12 Rolls | 48 Rolls |
| <u>Article</u> | <u>Roll size</u> | <u>Weight approx.</u> | <u>Packing unit</u> | <u>Rolls per pallet</u> | | | | | | | |
| 660-15 | 1,00 x 15,00 m | 375 g/m ² | 12 Rolls | 48 Rolls | | | | | | | |

*Compared to the classical plaster filling technique.

Version: 12/2021



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Roll-on-wall CoverStandard

Instructions of use

First step

Please check product prior to hanging. Irregularities in material are characteristic for this product. They do not entitle to claims. A control of the material and equal batch numbers is required. Claims after usage will not be accepted.

Wall surface

The wall surface must be dry and evenly absorbent. If necessary, treat prior to hanging.

Hanging

Use the glass fibre adhesive LECOLLE Xtra Strong observing manufacturer's instructions.

Cut wallpaper length to according height incl. 5 - 10 cm extra material. Front outside. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a rubber roller. Overlap and double cut or butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.


Painting

Once dry, the wallcovering can be wallpapered or painted with an adequate paint like dispersion, latex or acrylic paint according to DIN EN 13300. Please observe manufacturer's instructions. For further recommendations contact your local distributor.

Note

The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt, please test.

Version: 12/2021



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

