

# WallVision Product- and Environmental Declaration

**Brand: Boråstapeter**

**Collection: Anno**

**Ref. 4501 - 4550**

## Product

Wallcoverings made of nonwoven with weight between 75-190 g/sqm.

## Environmental mark

The wallpapers are CE-marked and fullfils the enviremental demands according to product standard SS-EN 15102:2007+A1:2011.

Fullfils the IGI:s trade standards

(IGI = International Wall covering Manufacturers' Association)

<http://www.igiwallcoverings.org/industry-standards/>

The wallcovering fulfils the productdemands of emissions according to M1 emission Class For Building Material.

Determination of the emission factor for VOC\* and identification of dominating substances has been made at the Swedish Testing- and Research Institute according to the FLEC-method\*\*. The test results is below the quantitative detection limit ( $< 10\mu\text{g}/\text{m}^2 \times \text{h}$ )

\* VOC=Volatile Organic Compounds

\*\* FLEC=Field and Laboratory Emission Cell

<http://www.rakennustieto.fi/index/english/emissionclassificationofbuildingmaterials.html>

## Product contents

All wallcoverings are free from PVC, heavy metals and other environmental harmful substances. All inks are waterbased.

The wallcoverings Components	Total weight percent	Weight-percent	Specifications of the components composition
Nonwoven	65-100%	40-85%	Cellulose (TCF)
		15-30%	Synthetic fibres+film
		0-30%	Vac/Acrylic polymer
		15-25%	Filler
Ink	0-35%	65-100%	Pigment Filler
		0-30%	Vac/Acrylic polymer

Formaldehyde in combined form exists naturally in wood being used in production of paper. Analysis of wallcovering therefore shows tracks of formaldehyde. The quantities though are essential lower than the valid limit.

The label of the wallcovering declares that the contents is less than the limits determined in the CE-standard for wallpapers. Even if the wallcovering is free from heavy metals it shall be written that it contains less then ( $<$ ) existing limit.

The label declares what DOP (Declaration Of Performance) that is valid for each ref. Can be found at [www.wallvision.se/CE](http://www.wallvision.se/CE)

## **Fireclass**

The wallcovering has a fireclass printed on the label that apply to the product standard and is judged according to EN13501-1. Fireclass of each ref. is shown at the end of this document.

## **Usage**

The wallcovering can be used in all areas except wet areas such as bathrooms etc. Suitable adhesive is a machine adjusted adhesive.

## **Colour fastness to light**

Very good colour fastness to light 6-8. The highest value is 8.

## **Packaging**

The wallcovering rolls are wrapped into a thin recyclable polyethylene film before being packed into a corrugated cardboard carton.

In average 50 gr packaging is being used per kg wallcovering.

The average transport volume (incl. packaging) per kg wallcovering is about 4 dm<sup>3</sup>.

WallVision is connected to the Swedish REPA-register

The packaging material is partly produced from recycled fibres.

## **Transport**

The wallcoverings are transported via trucks from our central warehouse in Borås, Sweden.

## **Care instructions**

The wallcoverings have high washability. Stains are treated as follows:

- Wet the stain with a cloth or a sponge using soapy water or detergent.
- Use plenty of lukewarm water to get off all soap rests.
- Wipe off the over amount of water and leave the wallcovering to selfdry.
- Avoid to get water in the joints where the wallcovering is unprotected.

## **Estimated lifetime**

Estimated lifetime of the wallcovering is 10-15 years..

## **Recycling and waste**

The wallcovering can be recycled as energy at combustion.

All excess inks are being reused in production.

No wallcovering waste is considered as hazardous waste.

In order to achieve and maintain necessary wallcovering strength and fullfil Wallvisions's quality standards no recycled material is included in the wallcovering.

## **Production**

When producing wallcovering, only enviremental friendly waterbased colors are being used. In that way We eliminate all kinds of dangerous waste. Wastewater from production is being taken care of at sight in a treatment plant and the mud that remains is burned upp by the Borås energy company.

## **Quality**

WallVision is certificated according to the international quality standard ISO 9001, certificate number 10 59.

## Certificates and reports

Ref. nr	Report	Match	Fireclass	Classification report firetest	M1 certificate
4501	38	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4502	38	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4503	38	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4504	26,5	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4505	17,67	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4506	17,67	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4507	53	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4508	53	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4509	53	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4510	53	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4511	53	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4512	17,67	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4513	17,67	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4514	26,5	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4515	26,5	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4516	26,5	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4517	53	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4518	53	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4519	53	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4520	53	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4521	38	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4522	38	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4523	38	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4524	38	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4525	17,67	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4526	17,67	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4527	17,67	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4528	6,6	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4529	6,6	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4530	6,6	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4531	6,6	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4532	38	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4533	38	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4534	38	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4535	17,67	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4536	17,67	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4537	17,67	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4538	53	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1

4539	53	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4540	53	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4541	32	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4542	32	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4543	32	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4544	32	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4545	32	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4546	32	Straight	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4547	38	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4548	38	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4549	38	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1
4550	38	Half drop	B-s1,d0	3. Decorative wallcovering nonwoven	WVM1:1