

**Product name:**

Crispy paper  
Item no. 5240xx-5270xx

**Product description:**

These products are printed using the screen printing, intaglio technique, embossing process

**Product specification:**

Length x width  
10.05 m x 0.53 m (5.33 m<sup>2</sup>)  
Diameter  
6.5 cm – 9.0 cm  
Roll weight  
1040 g – 1235 g (the total weight varies in accordance with the design, structure and quality of the wallpaper approx. 5%)

**Substrate/Support Material:**

Non- woven wallpaper 85 g/m<sup>2</sup>- 90 g/m<sup>2</sup>  
FSC- certified

**Product composition:**

The coating consists of:  
-PVC coating/screen printing ink  
    45-55 % PVC  
    25-35 % DINP  
    10-15 % calcium carbonate  
    Approx. 5 % titanium dioxide  
    Approx. 5 % additives  
-Intaglio ink  
-additional embossing

**Properties non woven:**

- RAL- inspected quality
- CE- compliant to EN 15102 : 2007 – A1 : 2011
- Flame-retardant to DIN EN 13501-1
- Water vapour-permeable to DIN 53122
- Highly water resistant
- No expansion/shrinkage
- When hung properly, completely dry strippable later

**Industrial standards:**

The manufacturing process complies with the RAL stipulations RAL GZ 479 produced by the "Gütegemeinschaft Tapete" ("Quality Association for Wallpaper") and the following European industrial standards:

EN 233  
Specification for finished wallpapers, wall vinyls and plastics wallcoverings

EN 235  
Wall coverings- Vocabulary and symbols

EN 12149  
Determination of migration of heavy metals and certain other elements, of vinyl chloride monomer and of formaldehyde release

EN 12956  
Determination of dimensions, straightness, spongeability and washability



<b>CE</b>	
0764	0765
Tapetenfabrik Gebr. Rasch GmbH & Co. KG Raschplatz 1   D-49565 Bramsche	
2014	
LE 04	
EN 15102 : 2007 – A1 : 2011	
Decorative wallcovering	
Reaction to fire class C-s1,d0	
Release of formaldehyde (Pascal)	
Release of heavy metals and specific elements	
Sh < 0.7 mg/kg	As < 0.5 mg/kg Ba < 1.5 mg/kg
Cd < 0.7 mg/kg	Cr < 0.7 mg/kg Pb < 0.7 mg/kg
Hg < 0.5 mg/kg	Se < 3.4 mg/kg
Release of vinyl chloride monomer < 0.2 mg/kg	

The respective performance declarations according to the product groups covered in EN 15102 have been created for all our products and can be viewed as a download from our website [ce.rasch.de](http://ce.rasch.de) Please enter the article number of the relevant product in the empty field.

**Manufacturer:**

Tapetenfabrik Gebr. Rasch GmbH & Co. KG  
Raschplatz 1  
49565 Bramsche  
Tel. +49 / 5461 / 81 10  
Fax +49 / 5461 / 81 1115  
[www.rasch.de](http://www.rasch.de)