

# WallVision Product- and Environmental Declaration

**Brand: Boråstapeter**

**Collection: Falsterbo III**

**Ref. 7650 - 7687**

## Product

Wallcoverings made of nonwoven with weight between 75 - 190 g/sqm.

## Environmental mark

The wallpapers are CE-marked and fullfills the enviremental demands according to product standard SS-EN 15102:2007+A1:2011.

Fullfills the IGI:s trade standards

(IGI = International Wall covering Manufacturers' Association)

<http://www.igiwallcoverings.org/industry-standards/>

The wallcovering fulfils the productdemands of emissions according to M1 emission Class For Building Material.

Determination of the emission factor for VOC\* and identification of dominating substances has been made at the Swedish Testing- and Research Institute according to the FLEC-method\*\*. The test results is below the quantitative detection limit ( $< 10\mu\text{g}/\text{m}^2 \times \text{h}$ )

<http://www.rakennustieto.fi/index/english/emissionclassificationofbuildingmaterials.html>

Emissionstest is made acording to ISO 16000-9, report with ref. 7P04269-3 + 7P04269-2

## Product contents

All wallcoverings are free from PVC, heavy metals and other environmental harmful substances. All inks are waterbased.

Tapetens komponenter	Vikt-%	CAS-nummer
Cellulosafibrer	35-50	
Polyesterfiber	10-20	
Styrenakrylatkopolymer	3-15	
Vinylacetatkopolymer	0,01-5	
Krita	8-23	1317-65-3
Kaolin	0,01-20	1332-58-7
Titandioxid	0,01-5	13463-67-7

Formaldehyde in combined form exists naturally in wood being used in production of paper. Analysis of wallcovering therefore shows tracks of formaldehyde. The quantities though are essential lower than the valid limit.

The label of the wallcovering declares that the contents is less than the limits determined in the CE-standard for wallpapers. Even if the wallcovering is free from heavy metals it shall be written that it contains less then ( $<$ ) existing limit.

The label declares what DOP (Declaration Of Performance) that is valid for each ref. Can be found at [www.wallvision.se/CE](http://www.wallvision.se/CE)

## **Fireclass**

The wallcovering has a fireclass printed on the label that apply to the product standard and is judged according to EN13501-1. Fireclass of each ref. is shown at the end of this document.

## **Usage**

The wallcovering can be used in all areas except wet areas such as bathrooms etc. Suitable adhesive is a machine adjusted adhesive.

## **Colour fastness to light**

Very good colour fastness to light 6-8. The highest value is 8.

## **Packaging**

The wallcovering rolls are wrapped into a thin recyclable polyethylene film before being packed into a corrugated cardboard carton.

In average 50 gr packaging is being used per kg wallcovering.

The average transport volume (incl. packaging) per kg wallcovering is about 4 dm<sup>3</sup>.

WallVision is connected to the Swedish REPA-register

The packaging material is partly produced from recycled fibres.

## **Transport**

The wallcoverings are transported via trucks from our central warehouse in Borås, Sweden.

## **Care instructions**

The wallcoverings have high washability. Stains are treated as follows:

- Wet the stain with a cloth or a sponge using soapy water or detergent.
- Use plenty of lukewarm water to get off all soap rests.
- Wipe off the over amount of water and leave the wallcovering to selfdry.
- Avoid to get water in the joints where the wallcovering is unprotected.

## **Estimated lifetime**

Estimated lifetime of the wallcovering is 10-15 years..

## **Recycling and waste**

The wallcovering can be recycled as energy at combustion.

All excess inks are being reused in production.

No wallcovering waste is considered as hazardous waste.

In order to achieve and maintain necessary wallcovering strength and fullfil Wallvisions's quality standards no recycled material is included in the wallcovering.

## **Production**

When producing wallcovering, only enviremental friendly waterbased colors are being used. In that way We eliminate all kinds of dangerous waste. Wastewater from production is being taken care of at sight in a treatment plant and the mud that remains is burned upp by the Borås energy company.

\* VOC=Volatile Organic Compounds

\*\* FLEC=Field and Laboratory Emission Cell

## Certificates and reports

Art.nr	Rapport	Passning	Brandklass	Klassningsrapport	M1 certifikat
7650	53	Half drop	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7651	53	Half drop	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7652	2,21	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7653	2,21	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7654	2,21	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7655	2,21	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7656	2,21	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7657	53	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7658	13,25	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7659	13,25	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7660	13,25	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7661	53	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7662	53	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7663	53	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7664	53	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7665	53	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7666	53	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7667	53	Half drop	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7668	53	Half drop	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7669	53	Half drop	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7670	10,6	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7671	10,6	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7672	10,6	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7673	10,6	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7674	6,63	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7675	6,63	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7676	6,63	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7677	53	Half drop	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7678	53	Half drop	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7679	53	Half drop	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7680	53	Half drop	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7681	53	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7682	53	Straight	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7683	0	Random	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7684	0	Random	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7685	0	Random	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7686	0	Random	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1
7687	0	Random	B-s1,d0	16. Decorative wallcovering nonwoven	WVM1:1