

TRAFFIC 203













TECHNICAL DATA SHEET

VINYL

Type of flooring EN 651 Vinyl floor covering on foam

Class of use EN 685 class 23  class 32 


Description

	EN 426	Length	25 m		High Professional Performance
	EN 426	Width	4+3*+2 m *3M Selection		Guarantee 15 years
	EN 428	Total thickness	2,0 mm		Surface Treatment EXTREME
	EN 429	Wear layer	0,4 mm		Antimicrobial Protection SANITIZED
	EN 430	Total weight	2,15 kg/sqm		Slip Resistant













EN 14041 : 2004

Delivered by: TARKETT GLD SA
Op der Sang 2, L-9779 LENTZWEILER

	EN 13501-1	Fire classification	B _{fl} -s1		EN 13893	Slip resistance	≥ 0,30 μ
		Report N°:	RA06-0063				

OPTIONAL CHARACTERISTICS

	ISO 105/B02	Light fastness	≥ 6		EN 1815	Static electrical propensity	≤ 2 kV
	EN 434	Dimensional stability	≤ 0,4%		EN ISO 717/2	Impact sound absorption	13 dB
	EN 433	Static indentation	≤ 0,20 mm		EN 12524	Thermal resistance for underfloor heating	Ok
	EN 660-1	Abrasion group	T			Anti-slip resistance	R10
	EN 425*	Castor chair	Ok		*		Ok

* fully adhered

Edition N°C/07-2008