

**Product name:**

Country Charme  
Item no. 447521-692709

-When hung properly, completely dry strippable later

**Product description:**

These products are printed using the screen printing, intaglio technique, embossing process

**Industrial standards :**

The manufacturing process complies with the RAL stipulations RAL GZ 479 produced by the "Gütegemeinschaft Tapete" ("Quality Association for Wallpaper") and the following European industrial standards:

**Product specification:**

Length x width  
10.05 m x 0.53 m (5.33 m<sup>2</sup>)  
Diameter  
6.8 cm – 9.0 cm  
Roll weight  
1069 g – 1317 g (the total weight varies in accordance with the design, structure and quality of the wallpaper approx. 5%)

EN 233  
Specification for finished wallpapers, wall vinyls and plastics wallcoverings

EN 235  
Wall coverings- Vocabulary and symbols

EN 12149  
Determination of migration of heavy metals and certain other elements, of vinyl chloride monomer and of formaldehyde release

**Substrate/Support Material:**

Non- woven wallpaper 70-85 g/m<sup>2</sup>, FSC-certified

EN 12956  
Determination of dimensions, straightness, spongeability and washability

**Product composition:**

The coating consists of:  
-PVC coating/screen printing ink  
    45-55 % PVC  
    25-35 % DINP  
    10-15 % calcium carbonate  
    Approx. 5 % titanium dioxide  
    Approx. 5 % additives  
-Intaglio ink  
-additional embossing



<b>CE</b>
<small>Tapetenfabrik Gebr. Rasch GmbH &amp; Co. KG Raschplatz 1   D 49565 Bramsche</small>
20
LE 04
EN 15102 : 2007 – A1 : 2011
Decorative wallcovering
<small>Reaction to fire class C – s1   d0 Release of formaldehyde Passed Release of heavy metals and specific elements Sb &lt; 1,0 mg/kg    As &lt; 1,0 mg/kg    Ba 2,0 mg/kg Cd &lt; 1,0 mg/kg    Cr &lt; 1,0 mg/kg    Pb &lt; 1,0 mg/kg Hg &lt; 1,0 mg/kg    Se &lt; 1,0 mg/kg Release of vinyl chloride monomer &lt; 0,2 mg/kg</small>

The respective performance declarations according to the product groups covered in EN 15102 have been created for all our products and can be viewed as a download from our website [ce.rasch.de](http://ce.rasch.de) Please enter the article number of the relevant product in the empty field.

**Properties Vlies:**

- RAL- inspected quality
- CE- compliant to EN 15102
- Flame-retardant to DIN EN 13501-1
- Water vapour-permeable to DIN 53122
- Highly water resistant
- No expansion/shrinkage

**Manufacturer:**

Tapetenfabrik Gebr. Rasch GmbH & Co. KG  
Raschplatz 1  
49565 Bramsche  
Tel. +49 / 5461 / 81 10  
Fax +49 / 5461 / 81 1115  
[www.rasch.de](http://www.rasch.de)

Bramsche, 12.01.2024