

## **DECLARATION OF PERFORMANCE**



DOP C4 6.0-0.55 ASPRC55

1.	Unique identification code of the product-type:			
	SPC RIGID CLICK 6.0mm / 0.55 mm wear layer			
2	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:			
	For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.			
3	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):			
	ASPECTA BV, Argon 37, 4751XC Oud Gastel, Netherlands			
4	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):			
•				
	_			
5	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:			
	System 3			
6	In case of the declaration of performance concerning a construction product covered by a harmonised standard:  Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).			
	reame of the notined test laboratory, that has issued the certificate of conformity of the factory production control, hispection reports and calculation reports (if relevant).			
	Entwicklungs- und Pruflabor Holztechnologie GmbH			
	is authorized as a notified body 0766 certificate FLO-24-06-17-02		not applicable	
	Notified Body		certificate of constancy of performance	
7	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:			
,	and the second of the second o			
	not applicable			
8	Declared performance			
	Essential characteristics	Performance	Harmonised technical specification	
	Reaction to fire	B <sub>ff</sub> - s1	EN 14041:2004+AC:2005+AC:2006	
	Content of Pentachlorophenol	NPD	EN 14041:2004+AC:2005+AC:2006	
	Formaldehyd Emissions	Class E1	EN 14041:2004+AC:2005+AC:2006	
	Slip resistance	DS	EN 14041:2004+AC:2005+AC:2006	
	Electrical behavior (dissipative)	NPD	EN 14041:2004+AC:2005+AC:2006	
	Electrical behavior (conductive)	NPD	EN 14041:2004+AC:2005+AC:2006	
	Electrical behavior (antistatic)	NPD	EN 14041:2004+AC:2005+AC:2006	
	Thermal conductivity [W/mK]	NPD	EN 14041:2004+AC:2005+AC:2006	
	Water-tightness	NPD	EN 14041:2004+AC:2005+AC:2006	
9.	The performance of the product identified in points 1 is in contral this declaration of performance is issued under the sole response.			
	Signed for and on behalf of the manufacturer by:	2. In a manufacture interface in politic		
	Graca Rocha , Sustainability & Quality Manager			
	(name and function)		Graca Pacles	
	Netherlands, June 2024		Graca Rocha	
	(place and date of issue)		(signature)	