

DECLARATION OF PERFORMANCE



DOP C4 6.0-0.55 ASPRC55

			GLOBAL
1.	Unique identification code of the product-type:		
	SPC RIGID CLICK 6.0mm / 0.55 mm wear layer		
2	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:		
	For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.		
3	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):		
	ASPECTA BV, Argon 37, 4751XC Oud Gastel, Netherland	S	
4	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):		
	-		
5	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:		
	System 3		
6	In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant		
	Entwicklungs- und Pruflabor Holztechnologie GmbH is authorized as a notified body 0766 certificate FLO-24-06-17-02		not applicable
	Notified Body		certificate of constancy of performance
7	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:		
	not applicable		
8	Della de de como de co		
Ü	Declared performance Essential characteristics	Performance	Harmonised technical specification
	Reaction to fire	B _f - s1	EN 14041:2004+AC:2005+AC:2006
	Content of Pentachlorophenol	NPD	EN 14041:2004+AC:2005+AC:2006
	Formaldehyd Emissions	Class E1	EN 14041:2004+AC:2005+AC:2006
	Slip resistance	DS	EN 14041:2004+AC:2005+AC:2006
	Electrical behavior (dissipative)	NPD	EN 14041:2004+AC:2005+AC:2006
	Electrical behavior (conductive)	NPD	EN 14041:2004+AC:2005+AC:2006
	Electrical behavior (antistatic)	NPD	EN 14041:2004+AC:2005+AC:2006
	Thermal conductivity [W/mK]	NPD	EN 14041:2004+AC:2005+AC:2006
	Water-tightness	NPD	EN 14041:2004+AC:2005+AC:2006
9.	The performance of the product identified in points 1 is in co. This declaration of performance is issued under the sole res. Signed for and on behalf of the manufacturer by:	I onformity with the declared performance in point 8.	
	Graca Rocha , Sustainability & Quality Manager		
	(name and function)		Graca Rocha
	Netherlands, June 2024		
	(place and date of issue)		(signature)