

DECLARATION OF PERFORMANCE



DOP C4 5.2-0.55 ASPRC55

			GLOBAL	
1.	Unique identification code of the product-type:			
	SPC RIGID CLICK 5.2mm / 0.55 mm wear layer			
2	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specific cation, as foreseen by the manufacturer:			
	For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.			
3	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):			
	ASPECTA BV, Argon 37, 4751XC Oud Gastel, Netherlands			
4	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):			
	-			
5	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:			
	System 3			
6 In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if i				
	,	, , , ,		
	Entwicklungs- und Pruflabor Holztechnologie GmbH			
	is authorized as a notified body 0766 certificate FLO-24-06-17-02		not applicable	
	Notified Body		certificate of constancy of performance	
7	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:			
	not applicable			
8	Declared performance			
	Essential characteristics	Performance	Harmonised technical specification	
	Reaction to fire	B _{fl} ⁻ s1	EN 14041:2004+AC:2005+AC:2006	
	Content of Pentachlorophenol	NPD	EN 14041:2004+AC:2005+AC:2006	
	Formaldehyd Emissions	Class E1	EN 14041:2004+AC:2005+AC:2006	
	Slip resistance	DS	EN 14041:2004+AC:2005+AC:2006	
	Electrical behavior (dissipative)	NPD	EN 14041:2004+AC:2005+AC:2006	
	Electrical behavior (conductive)	NPD	EN 14041:2004+AC:2005+AC:2006	
	Electrical behavior (antistatic)	NPD	EN 14041:2004+AC:2005+AC:2006	
	Thermal conductivity [W/mK]	NPD	EN 14041:2004+AC:2005+AC:2006	
	Water-tightness	NPD	EN 14041:2004+AC:2005+AC:2006	
9.	The performance of the product identified in points 1 is in cor	oformity with the declared performance in point 8		
	This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3			
	Signed for and on behalf of the manufacturer by:			
	Graca Rocha , Sustainability & Quality Manager			
	(name and function)		C	
	Netherlands, June 2024		Graca Rocha	
	(place and date of issue)		(signature)	